



Novojunta® Decor Aluminum



Novojunta® Decor Aluminio is a solution for expansion joints made of anodized or natural aluminum with a central body made of EPDM rubber. The excellent properties of the EPDM allow the profile to absorb expansion and contraction movements, preventing from the apparition of pathologies. It is available in a wide range of heights. It is delivered with protective film on the visible side to avoid damage during the handling or transport.


General features

Material: Aluminum + EPDM rubber

Length: 2,5 m.l. (8ft2in)

Packaging: 10, 20 or 4 u./box

Color



Sizes:

h:	9,5 3/8"	12 1/2"	15 9/16"	20 3/4"	41 1 5/8"	51 2"	126 5"
a:	12.5 1/2"						
A.M:	+1 +0.039"	+1 +0.039"	+1 +0.039"	+1 +0.039"	+1.2 +0.047"	+1.2 +0.047"	+1.2 +0.047"
A.T.M:	-2 -0.079"	-2 -0.079"	-2 -0.079"	-2 -0.079"	-3.5 -0.138"	-3.5 -0.138"	-3.5 -0.138"
A.T.M:	3 1/8"	3 1/8"	3 1/8"	3 1/8"	4.7 3/16"	4.7 3/16"	4.7 3/16"

A.M: Allowed movement (mm.) A.T.M: Allowed total movement (mm.)

Applications

Novojunta® Decor aluminum is a solution for expansion joints whose main function is to absorb expansion and contraction movements proceeding from floorings or tiled walls to avoid the apparition of pathologies. It can be installed vertically and horizontally in floorings or tiled walls.

Technical Features and Tests

Alloy: 6063 (AA y ASTM)
L-3441 (UNE 38-301-89)

Fire resistance: M0 (UNE 23-727-90)

Abrasion resistance: High

Lightfastness: Excellent

Appearance and color: EN 12373-1

Materials



Aluminum **Novojunta® Decor aluminum** is a profile made by extrusion of aluminum. It has been anodized, improving mainly by this process its corrosion and mechanical resistance and its appearance. The anodized applied, has the quality seal "Qualanod" which guarantees the quality of the process and the resulting profiles. This seal regulates several tests: appearance and color, thickness measurements, sealing and impregnation control, abrasion resistance, lightfastness, acetic saline chamber and nitric acid immersion.

Aluminum is a material with excellent chemical, physical and mechanical properties. It is lightweight, tough, ductile, malleable and highly durable.

EPDM The central body of Novojunta® Decor Aluminum is made of high quality EPDM rubber. EPDM is an elastomer polymer with excellent mechanical properties. It has good resistance to abrasion, wear and impact, is a good insulator, and resists weathering, common chemicals and has a wide working temperature range. Its excellent compression set is the main feature in absorbing the deformations and geometric variations of constructive elements.

Recommendations of installation

Emac®, in his awareness for the correct execution of the ceramic systems, took part in the committee for the elaboration of the UNE 138002: 2017 standard "General rules for the execution of ceramic tile systems by adhesion". In that UNE standard the recommendations of installation for expansion joints were defined as follow:

Installation	Separation distance / Area	Joint width (mm)
<i>Linear expansion joints</i>		
<i>Outdoor walls</i>	Each 3 - 4 ml max. Regular areas max. 16 m ²	≥ 8 mm
<i>Outdoor floors</i>	Each 2,5 - 5 ml max. Regular areas max. 16 m ²	
<i>Indoor floors</i>	Respect open contraction joints Each 8 ml maximum Regular areas max. 40 m ²	≥ 5 mm
<i>Singular points</i>	Door treshold Floor changes	≥ 8 mm
<i>Perimeter expansion joints</i>		
<i>Indoor walls</i>	Perimeter joints Wall / Ceiling Wall / Wall	≥ 5 mm ≥ 8 mm
<i>Outdoor walls</i>	Indoor / outdoor edges	≥ 8 mm
<i>Indoor floors</i>	Perimeter joints and encounters with elements	
<i>Outdoor floors</i>	Perimeter joints and encounters with elements	
<i>Singular points</i>	Encounter joints with joinery	≥ 5 mm

These recommendations are the minimum dimensions to take into account. The particularities of each project could make necessary to place the joints at less distance. The expansion joints should be planned since the project phase. The correct design and dimensionement of the expansion joints, together with an adequate choice of materials and a correct installation execution, will help to prevent from the apparition of pathologies.

Installation



To see the video, capture this image with your mobile phone (QR code reader software is necessary) or click on it.

1. Spread a big amount of thin-set mortar on the surface to be tiled.
2. Then, place the profile and press it so the thin-set mortar could pass through the holes of the anchoring wing.
3. Place one tile over the anchoring wing and press it to get an optimal joint between the thin-set mortar and the profile.
4. Repeat the last step placing tiles along the profile (both sides) until the installation is finished. Before it cures, hit softly with a rubber hammer to align the profile with the tiles.
5. Finally, clean the leftover material, remove the protective film and let dry.

* If you're going to polish the flooring, install this profile slightly below the tile to avoid possible damage.



Cleaning and maintenance

The cleaning must be done periodically with a soft cloth. If you use a neutral liquid cleaner, you must rinse the profile with cold water and dry to remove excess moisture. If dirtiness persists, clean the profile with a solution with clean water and detergent or neutral soap 5%, brushing with a cloth that has no particles that could scratch the finish. Ensure the lacquered surface is totally cold (maximum 20°C) before the cleaning.

Steel wool, abrasive cleaners, souring products as well as strong acids (hydrochloric and perchloric), strong bases (caustic soda or ammonia) or carbonated solutions are not recommended. Citric acid is neither recommended because it dissolves the protective layer of the surface of aluminium. Waxes, petrolatum, lanolin or similar substances are not appropriate. Solvents containing haloalkanes (hydrofluoroether and chlorinated solvents) and curing accelerators containing chlorides should not be used (use special accelerators free of chlorides)

Technical Information

You can find out more information about the technical features of Emac®'s products by downloading their Technical Files in www.emac.es.

If you have any query, please contact our Technical Department in tecnico@emac.es.



Outdoors



Indoors



Wall tiling



Flooring

Emac Complementos S.L. (Spain) info@emac.es // Emac America L.L.C. (FL,USA) info@emac-america.com // Emac Italia S.R.L. (Italy) info@emac-italia.it

www.emac.es

*The data provided are for information only and have been obtained by our supplier or Emac®.
Does not constitute legal guarantee in terms of properties and / or functionality of the application of material*